

MODEL 74: 5/8-18  
MODEL 74M: M18-1



## MODEL NUMBER

74-13568-C2

## PRODUCT LINE


GO™ Switch 70 Series Straight

## SPECIFICATIONS

|                        |                           |
|------------------------|---------------------------|
| Model                  | 74 Model                  |
| Contact Form           | SPDT                      |
| Sensing Range          | 0.100" end sensing        |
| Outlet Position        | Bottom of enclosure       |
| Enclosure Material     | 316L SS, 2000 PSI         |
| Area Classification    | UL General Purpose        |
| Wiring Option          | QDC, micro, 3 pin         |
| Regional Certification | No Regional Certification |
| Custom Field           |                           |


## WIRING DIAGRAM

3 PIN MICRO CONNECTOR — DBA  
SPST FORM C



PIN 1 — COM (GREEN)  
PIN 2 — N/C (RED/BLACK)  
PIN 3 — N/O (RED/WHITE)

## NAMEPLATE



Type 4X  
120VAC/4A; 24VDC/3A

**GO**  
SWITCH

Current as of July 20, 2017 – Subject to change without notice.

**TOPWORX**  
Pneutrol International Limited  
UK Office  
5 Caulside Drive, Antrim, BT41 2DU  
United Kingdom  
TEL: +44 (0) 28 9448 1800  
www.pneutrol.com/industrialspares

**Pneutrol**  
Leading Industrial Solutions  
sales@pneutrol.com  
European Office  
Unit 6, Saint Anthony's Business Park, Ballymount Road, D22 VW95  
Ireland  
TEL: +353 (0) 1 4373653  
www.pneutrol.com/industrialspares