

# Single subbase, for soft-start valve

- Compressed air connection output G 1/2



|                                |                     |
|--------------------------------|---------------------|
| Working pressure min./max.     | -1 ... 16 bar       |
| Ambient temperature min./max.  | -20 ... 70 °C       |
| Medium temperature min./max.   | -20 ... 70 °C       |
| Medium                         | Compressed air      |
| Number of valve positions max. | 1                   |
| Exhaust (3,5)                  | uncollected exhaust |
| Exhaust type                   | Ports separated     |
| Weight                         | 0,34 kg             |

## Technical data

| Part No.   | Compressed air connection<br>Input<br>[1] | Compressed air connection<br>Output<br>[2 / 4] |
|------------|---|--|
| 5834710000 | G 1/2                                     | G 1/2  |

| Part No.   | Compressed air connection<br>Exhaust<br>[3 / 5] | Compressed air connection<br>Pilot connection<br>[X] |
|------------|---|--|
| 5834710000 | G 1/2   | G 1/8  |

## Technical information

The min. control pressure must be adhered to, since otherwise faulty switching and valve failure may result!

The pressure dew point must be at least 15 °C under ambient and medium temperature and may not exceed 3 °C .

The oil content of compressed air must remain constant during the life cycle.

Use only the approved oils from AVENTICS. Further information can be found in the "Technical information" document (available in the MediaCentre).

## Technical information

### Material

|            |                                  |
|------------|----------------------------------|
| Base plate | Die-cast aluminum, black painted |
|------------|----------------------------------|

## Dimensions

### Dimensions

