



# 5/2-directional valve, Series 581, size 3

- ISO 5599-1
- ISO 3
- 5/2
- With spring return
- $Q_n = 4800$  l/min
- Compressed air connection output Base plate ISO 5599-1
- suitable for ATEX



Version	Spool valve
basic valve with electrical connector	Basic valve without pilot valve
Pilot	external internal
Sealing principle	Soft sealing
Blocking principle	Single base plate principle
Connection type	Plate connection
Standards	ISO 5599-1, ISO 3
ATEX class G	2G Ex mb II T4
ATEX class D	2D Ex tD A21 T130°C
Working pressure min./max.	-0,95 ... 16 bar
Control pressure min./max.	3 ... 16 bar
Ambient temperature min./max.	-20 ... 70 °C
Medium temperature min./max.	-20 ... 70 °C
Medium	Compressed air
Max. particle size	50 µm
Oil content of compressed air	0 ... 5 mg/m <sup>3</sup>
Nominal flow $Q_n$	4800 l/min
Flow conductance C	18,9 l/(s*bar)
Protection class with connection	IP65
Duty cycle	100 %
Mounting screw	with hexagon socket
Mounting screw tightening torque	10 Nm
Weight	0,85 kg

## Technical data

Part No.		Throttle
5813180000		-
5813181000		with throttle

Nominal flow  $Q_n$  at 6 bar and  $\Delta p = 1$  bar, An operating pressure of up to 16 bar is possible in the version with manual override without detent., Internal pilot: min./max. operating pressure is the same as min./max. control pressure

## Technical information

The min. control pressure must be adhered to, since otherwise faulty switching and valve failure may result!  
The pressure dew point must be at least 15 °C under ambient and medium temperature and may not exceed 3 °C .  
The oil content of compressed air must remain constant during the life cycle.  
Use only the approved oils from AVENTICS. Further information can be found in the "Technical information" document (available in the MediaCentre).

\* Note: ATEX version can be produced by combining the basic valve without coil with a series DO30 CNOMO pilot valve and an ATEX coil. ATEX ID: see ATEX coils catalog page.

## Technical information

Housing	Aluminum
Seals	Acrylonitrile butadiene rubber

## Dimensions

### Dimensions

