

Coil, series CO1

- With valve plug connector
- Coil width 30 mm
- Power consumption DC 2,1 W
- ATEX



| | |
|-------------------------------|------------------------------|
| Certificates | ATEX |
| ATEX class G | II 3G Ex nA IIC T4 Gc X |
| ATEX class D | II 3D Ex tc IIIC T125°C Dc X |
| Ambient temperature min./max. | -10 ... 50 °C |
| Protection class | IP65 |
| Duty cycle ED | 100 % |
| Compatibility index | 13 |
| Weight | See table |

Technical data

| Part No. | Operationalvoltage | Operationalvoltage | Operationalvoltage | Voltage tolerance |
|------------|--------------------|--------------------|--------------------|-------------------|
| | DC | AC 50 Hz | AC 60 Hz | DC |
| R412000147 | - | 230 V | 230 V | - |
| R412000144 | 24 V | - | - | -10% / +10% |

| Part No. | Voltage tolerance | Voltage tolerance | Power consumption | Holding power |
|------------|-------------------|-------------------|-------------------|---------------|
| | AC 50 Hz | AC 60 Hz | DC | AC 50 Hz |
| R412000147 | -20% / +10% | -10% / +20% | - | 4,1 VA |
| R412000144 | - | - | 2,1 W | - |

| Part No. | Switch-on power | Weight |
|------------|-----------------|----------|
| | AC 50 Hz | |
| R412000147 | 4,1 VA | 0,137 kg |
| R412000144 | - | 0,14 kg |

Dimensions

Dimensions

