










# 5/2-directional valve, Series 581, size 4

- ISO 5599-1
- ISO 4
- 5/2
- Qn = 6000 l/min
- Compressed air connection output Base plate ISO 5599-1
- Electrical connection Plug, EN 175301-803, form A
- Manual override with detent, without detent



Version	Spool valve
Sealing principle	Soft sealing
Blocking principle	Single base plate principle
Connection type	Plate connection
Standards	ISO 5599-1, ISO 4
Working pressure min./max.	See table below
Control pressure min./max.	1,5 ... 10 bar
Ambient temperature min./max.	-15 ... 50 °C
Medium temperature min./max.	-15 ... 50 °C
Medium	Compressed air
Max. particle size	50 µm
Oil content of compressed air	0 ... 5 mg/m <sup>3</sup>
Nominal flow Qn	6000 l/min
Flow conductance C	24,5 l/(s*bar)
Protection class with connection	IP65
Compatibility index	14
Duty cycle	100 %
Typ. switch-on time	21 ms
Typ. switch-off time	21 ms
Mounting screw	with hexagon socket
Mounting screw tightening torque	10 Nm
Weight	1,57 kg

## Technical data

Part No.		MO	Operationalvoltage DC	Operationalvoltage AC 50 Hz	Voltage tolerance DC
5814290650			24 V	-	-10% / +10%
5814290450			-	230 V	-
5814291650			24 V	-	-10% / +10%
5814291450			-	230 V	-
5814292650			24 V	-	-10% / +10%
5814292450			-	230 V	-
5814293650			24 V	-	-10% / +10%
5814293450			-	230 V	-

Part No.	Voltage tolerance AC 50 Hz	Power consumption DC	Holding power AC 50 Hz	Switch-on power AC 50 Hz
5814290650	-	2 W	-	-

Part No.	Voltage tolerance AC 50 Hz	Power consumption DC	Holding power AC 50 Hz	Switch-on power AC 50 Hz
5814290450	-10% / +10%	-	4,8 VA	7 VA
5814291650	-	2 W	-	-
5814291450	-10% / +10%	-	4,8 VA	7 VA
5814292650	-	2 W	-	-
5814292450	-10% / +10%	-	4,8 VA	7 VA
5814293650	-	2 W	-	-
5814293450	-10% / +10%	-	4,8 VA	7 VA

Part No.	Pilot	Working pressure min./max.	Compatibility index
5814290650	internal	1,5 ... 10 bar	14
5814290450	internal	1,5 ... 10 bar	14
5814291650	internal	1,5 ... 10 bar	14
5814291450	internal	1,5 ... 10 bar	14
5814292650	external	-0,95 ... 10 bar	14
5814292450	external	-0,95 ... 10 bar	14
5814293650	external	-0,95 ... 10 bar	14
5814293450	external	-0,95 ... 10 bar	14

Part No.	Electrical connection Pilot valve	Throttle
5814290650	Plug EN 175301-803, form A	-
5814290450	Plug EN 175301-803, form A	-
5814291650	Plug EN 175301-803, form A	with throttle
5814291450	Plug EN 175301-803, form A	with throttle
5814292650	Plug EN 175301-803, form A	-
5814292450	Plug EN 175301-803, form A	-
5814293650	Plug EN 175301-803, form A	with throttle
5814293450	Plug EN 175301-803, form A	with throttle

Nominal flow  $Q_n$  at 6 bar and  $\Delta p = 1$  bar, MO = Manual override, An operating pressure of up to 16 bar is possible in the version with manual override without detent.

## Technical information

The min. control pressure must be adhered to, since otherwise faulty switching and valve failure may result!

The pressure dew point must be at least 15 °C under ambient and medium temperature and may not exceed 3 °C .

The oil content of compressed air must remain constant during the life cycle.

Use only the approved oils from AVENTICS. Further information can be found in the "Technical information" document (available in the MediaCentre).

## Technical information

Housing	Aluminum
Seals	Acrylonitrile butadiene rubber

## Dimensions

### Dimensions

