

Compressed air tubing, Series TU1-F-PUR

- Ø 10 mm
- Polyether polyurethane
- suitable for use in food processing
- Max. working pressure at 20 °C 10 bar



Max. working pressure at 20 °C 10 bar
 Ambient temperature min./max. -30 ... 60 °C
 Weight See table below

Technical data

Part No.	external	Wall thickness	Color	Length	Bending radius min.
	-Ø			Delivery unit	At 20 °C
R412009964	10 mm	1,5 mm	Black translucent	25 m	40 mm
R412007418	10 mm	1,5 mm	Silver gray	25 m	40 mm
R412004798	10 mm	1,5 mm	Blue translucent	25 m	40 mm
R412004799	10 mm	1,5 mm	Transparent	25 m	40 mm
R412014560	10 mm	1,5 mm	Translucent red	100 m	40 mm
R412007419	10 mm	1,5 mm	Silver gray	100 m	40 mm
R412009994	10 mm	1,5 mm	Blue translucent	100 m	40 mm

Part No.	Weight per meter
R412009964	0,046 kg
R412007418	0,046 kg
R412004798	0,046 kg
R412004799	0,046 kg
R412014560	0,05 kg
R412007419	0,046 kg
R412009994	0,046 kg

price / m

Technical information



External calibrated
Suitable for dynamic laying
Approved for food (documented by manufacturer declaration)
Resistant to microbes
Excellent hydrolysis characteristics

Technical information

Material

Material	Polyether polyurethane
----------	------------------------