

QR1-S standard series

- Y-Plug connector, reducing
- push-in fitting
- Ø1/4 Ø3/8 Ø1/2 Ø5/16
- push-in fitting
- Ø5/32 Ø5/16 Ø3/8 Ø1/4
- QR1-S-RYR



Working pressure min./max.	-0,95 ... 10 bar
Ambient temperature min./max.	0 ... 60 °C
Weight	See table below

Technical data

Part No.	Port G	Port D	Delivery unit	Weight
R432000273	Ø1/4	Ø5/32	10 piece	0,014 kg
R432000276	Ø3/8	Ø5/16	10 piece	0,018 kg
R432000271	Ø1/2	Ø3/8	10 piece	0,027 kg
R432000272	Ø5/16	Ø1/4	10 piece	0,009 kg
R432000274	Ø3/8	Ø1/4	10 piece	0,032 kg

Weight per piece

Technical information

The series QR1 (plastic) and QR2 (metal) can not be combined
These pneumatic components with NPT or inch thread dimensions are only available from our US sales organization.

For further information about assembling and tolerances of adaptable tubing can be found in the "Technical information" document (available in the MediaCentre).


Technical information

Material	
Material	nickel-plated
Housing	Polybutyleneterephthalate
Seal	Acrylonitrile butadiene rubber
Tooth lock washer	Stainless steel

Material	
Release ring	Polyoxymethylene
Release ring holder	Die cast zinc Brass, nickel-plated

Dimensions

Dimensions in inches



Dimensions in inches

Part No.	Port D	Port G	A	B1	B2	J	X1	X2	Y1	Y2
R432000273	Ø5/32	Ø1/4	1.45	0.67	0.67	0.42	0.55	0.47	0.47	0.39
R432000276	Ø5/16	Ø3/8	1.95	0.73	0.83	0.55	0.75	0.63	0.67	0.55
R432000271	Ø3/8	Ø1/2	2.12	0.83	0.89	0.71	0.91	0.75	0.83	0.67
R432000272	Ø1/4	Ø5/16	1.6	0.67	0.73	0.47	0.63	0.55	0.55	0.47
R432000274	Ø1/4	Ø3/8	1.95	0.69	0.76	0.71	0.75	0.55	0.67	0.47